

# 21.5" marine monitor

Panel mount (Flush Mount) MP-21.5



The 21.5" rugged marine panel mount (Flush Mount) monitor is specially engineered to survive from the most demanding working environment.

The front-mounted sunlight readable touch screen makes the industrial rugged marine monitor vividly and user-friendly. In addition, the high power efficiency and low heat design guarantee the stability and longevity required for mission critical deployment.

## Features:

- 1000 nits Sunlight Readable LCD(0 - 100% Brightness adjustment)
- IP65 waterproof front side
- High bright 1000 NIT Low Power LED Backlights
- Sunlight Readable (optical bond & AR enhancements)
- Rugged Light Weight steel or aluminum Chassis
- High Shock & Vibration Resistance
- Protective Marine/Vehicle Power Supply
- Long Life, Low Power Consumption LED Backlight
- Wide Operating Temperature
- Advanced Optical Bonding (AOT)
- High Shock & Vibration Resistance
- Application: Marine

## Specification:

<b>Size</b>	<b>21.5"</b>
<b>Model</b>	MP-21.5
<b>Aspect Ratio</b>	16:9
<b>Resolution</b>	1920 x 1080
<b>Response Time</b>	8 ms
<b>Viewing area(mm)</b>	268.1 x 476.6
<b>Viewing Angle</b>	170 (H), 170(V)
<b>Contrast Ratio</b>	1000:1
<b>Brightness</b>	1000 nits with deep diming ( 250nits for optional)
<b>Touchscreen</b>	Standard type no touch (Glass protection for front side)
	Options: resistance or capacitance touch screen (USB/RS232)

<b>IP Rating</b>	IP65 for front side
<b>Video Inputs</b>	1 x VGA Options: DVI,HDMI,AV
<b>Power consumption</b>	12V DC 45W Options: 8 to 36V DC or 100~240V AC
<b>Control Buttons</b>	Manual Brightness controlling and OSD menu in backside( with Power, Menu, Adjust +/- on back)
<b>Mounting</b>	Panel mount (Flush Mount) and VESA 75mm mount
<b>Temperature</b>	Operating -20 to 60C Storage -30 to 80C
<b>Unit Weight(kg)</b>	7
<b>Dimensions(mm)</b>	330 x 538 x 45.5

### Dimension:



### Installation:

